

Wyse® V10L Dual-DVI™ Thin Client

WYSE
| | | |

Fact sheet



Designed to Perform in Data-driven Environments.

The Wyse® Thin OS™ powered Wyse V10L Dual-DVI thin client is the most optimized solution for Citrix XenApp, Microsoft RDP (Terminal Services), and VMware VDI environments. The Wyse V10L Dual-DVI comes with an ultra-thin operating system that boots in seconds, automatically updates itself, and delivers the administrative simplicity that IT departments need.

With dual digital video outputs for better conformity between displays and ideal for advanced client virtualization environments, this is now the most powerful & innovative offering in the Wyse Thin OS product line. The Wyse V10L Dual-DVI delivers the performance end-users need – two DVI-I connectors for easy connectivity to two full digital displays or two VGA displays, 128MB Flash, 256MB DDR RAM, plus serial, and three USB ports. Using the same form-factor as the Wyse V class family, the Wyse V10L Dual-DVI thin client can fit easily into most work environments.

At a glance:

User Experience

- Fast and responsive performance
- Simple and fast to install, connect, and use out of the box
- No motors results in lower power consumption, quiet operation, and ultra-high reliability
- ICA version 10.x compatibility
- Built-in support for Wyse TCX virtualization technologies

Enterprise Security

- No data is stored on the thin client, so it cannot be lost or stolen
- Smart card support

Connectivity

- Connects to two DVI or VGA type displays
- 3 USB ports
- Fast LAN access

Management

- Automatic configuration and updating via DHCP options and FTP
- Integrates with Wyse Device Manager for minimal day-to-day on-going support and remote monitoring

Wyse V10L Dual-DVI™ Thin Client

Specifications

Processor	Via C7 Eden 800MHz
Memory	128MB Flash/256MB DDR RAM
I/O peripheral support	Two DVI-I Ports for direct connection to digital displays Two DVI-I Port to VGA (DB-15) Adapters for use with analog displays Enhanced USB keyboard with PS/2 mouse port and Windows keys PS/2 mouse included One serial port Three USB 2.0 ports (1 on front, 2 on back)
Networking	10/100 Base-T Fast Ethernet port (RJ-45)
Display	VESA monitor support with Display Data Control (DDC) for automatic setting of resolution and refresh rate Dual Monitors at 32-bit color or 24-bit color up to: 1920x1200@60 Hz
Audio	Output: 1/8-inch mini, full 16-bit stereo, 48KHz sample rate Input: 1/8-inch, 8-bit mini microphone
Options	Internal Smart Card reader
Physical characteristics	Height: 7.9" (201mm) Width: 1.8" (46mm) Depth: 7.1" (180mm) Shipping Weight: 8 lbs. (3.6kg)
Mountings	Vertical foot (optional horizontal feet) Optional VESA mounting bracket Built-in Kensington security slot (cable sold separately)
Power	Worldwide auto-sensing 100-240 VAC, 50/60 Hz Average power usage with device connected to 1 keyboard with 1 PS/2 mouse and 1 monitor: 17.2 Watts
Temperature Range	Horizontal position: 50° to 95° F (10° to 35° C) Vertical position: 50° to 104° F (10° to 40° C)
Security	Kensington lock slot
Safety Certifications	German EKI-ITB 2000, ISO 9241-3/-8 cULus 60950, TÜV-GS, EN 60950 FCC Class B, CE, VCCI, C-Tick WEEE, RoHS Compliant
Warranty	Three-year limited warranty

Wyse Technology Inc.
3471 North First Street
San Jose, CA 95134-1801

Visit our website at:
<http://www.wyse.com>
Or send email to:
sales@wyse.com

Wyse Sales
800 GET WYSE
(800 438 9973)

**Wyse Customer
Service Center:**
800 800 WYSE
(800 800 9973)

WYSE
| | | |

Wyse V10L Dual-DVI™ Thin Client



Wyse Technology Inc.
3471 North First Street
San Jose, CA 95134-1801

Visit our website at:
<http://www.wyse.com>
Or send email to:
sales@wyse.com

Wyse Sales
800 GET WYSE
(800 438 9973)

**Wyse Customer
Service Center:**
800 800 WYSE
(800 800 9973)